

## Cartridge Filters - 36 Sq Ft Diatomaceous Earth (DE) Filter (short)

Item APF036PRO



### PRODUCT DESCRIPTION

Remove dirt and debris down to 5 microns our high performance D.E. series filters. These Eco friendly solutions are an upgrade to standard sand filters and require minimal maintenance.

### FEATURES

- ▶ Universally compatible NTP setup provides hassle-free installation and maintenance.
- ▶ Single D.E. (Diatomaceous Earth) element.
- ▶ 2 NPT female fittings.
- ▶ Quick change cartridge filters with 1/2 turn secure-n-lock replacement.
- ▶ Easy-to-read pressure gauge allows for quick performance assessment.
- ▶ Works well with low speeds.
- ▶ Large drain plug.
- ▶ Constructed of corrosion-proof reinforced thermoplastic tank for long service life.
- ▶ Manual air relief valve pre-installed from the factory.
- ▶ 6 ft. Cord with a standard plug.

### APPLICATIONS

- ▶ Above Ground and In-Ground Pool and Spa

### TECHNICAL DATA

General	
Model Number	APF036PRO
Description	36 Sq Ft Diatomaceous Earth (DE) Filter (short)
UPC Code	816965015818
Brand	Intermatic
Country of Origin (Intermatic)	U.S.A.
Warranty Period	1-Year limited
Filter Area (Sq Ft)	36
Min Service Clearance	39"
Filter Element Height	26 5/8"
Cartridges Required	1
Diatomaceous Earth Required	3.5 lbs
Turnover Capacity 6 hour (gallons)	25,920
Turnover Capacity 8 hour (gallons)	34,560
Turnover Capacity 10 hour (gallons)	43,200
Max Working PSI	50
Replacement Filter Element	62559-AQP1
Turnover Capacity 6 hour Max Flow (gallons)	32,400
Turnover Capacity 8 hour Max Flow (gallons)	43,200
Turnover Capacity 10 hour Max Flow (gallons)	54,000
Maximum Flow Rate (GPM)	90

### Material Specifications

Color	Black
-------	-------

Packaging

Shipping Weight (lbs)	29
Unit Carton Dimensions (H x W x L) in	25.5 x 16.5 x 16.5 in
Unit Package Quantity	1

Operating Specifications

Recommended Water Flow GPM	72
----------------------------	----

Standards and Certifications

California Proposition 65	DEHP
RoHS Certification	X