

## PVC True Union Ball Valves - Standard Series - HDPE/EPDM

### Válvulas de bola en PVC doble unión - Standard Series - HDPE/EPDM



#### Solvent socket and threaded

##### Cementar y roscar

Seats / asientos: HDPE  
O-rings / juntas: EPDM  
240 psi @ 73°F



| Size   | Reference   | psi | Pack | Weight (lb) | Q       | Code         |
|--------|-------------|-----|------|-------------|---------|--------------|
| 1/2"   | 05 60 801 D | 240 | B    |             | 20 (10) | <b>21997</b> |
| 3/4"   | 05 60 802 D | 240 | B    |             | 10 (5)  | <b>21998</b> |
| 1"     | 05 60 803 D | 240 | B    |             | 8       | <b>21999</b> |
| 1 1/4" | 05 60 804 D | 240 |      |             |         | <b>22000</b> |
| 1 1/2" | 05 60 805 D | 240 | C    |             | 6       | <b>22001</b> |
| 2"     | 05 60 806 D | 240 | D    |             | 8       | <b>22002</b> |



Seats / asientos: HDPE<sup>2</sup>  
O-rings / juntas: EPDM  
150 psi @ 73°F

#### SOCKET - CEMENTAR

| Size       | Reference    | psi | Pack | Weight (lb) | Q     | Code         |
|------------|--------------|-----|------|-------------|-------|--------------|
| 2 1/2"     | 05 60 907 MA | 150 | D    |             | 4 (1) | <b>06620</b> |
| 3"         | 05 60 908 MA | 150 | D    |             | 2 (1) | <b>07088</b> |
| 4" (DN 80) | 05 60 910 MA | 150 | D    |             | 2 (1) | <b>07377</b> |
| 4"         | 05 60 911 MA | 150 | D    |             | 1     | <b>22068</b> |

#### THREADED - ROSCAR

| Size       | Reference | psi | Pack | Weight (lb) | Q     | Code         |
|------------|-----------|-----|------|-------------|-------|--------------|
| 2 1/2"     | 05 60 807 | 150 | D    |             | 4 (1) | <b>07095</b> |
| 3"         | 05 60 808 | 150 | D    |             | 2 (1) | <b>07096</b> |
| 4" (DN 80) | 05 60 810 | 150 | D    |             | 2 (1) | <b>07378</b> |
| 4"         | 05 60 811 | 150 | D    |             | 1     | <b>22067</b> |

## PVC True Union Ball Valves - Standard Series - PTFE/EPDM

### Válvulas de bola en PVC doble unión - Standard Series - PTFE/EPDM



#### Solvent socket and threaded

##### Cementar y roscar

Seats / asientos: PTFE  
O-rings / juntas: EPDM  
240 psi @ 73°F



| Size   | Reference   | psi | Pack | Weight (lb) | Q       | Code         |
|--------|-------------|-----|------|-------------|---------|--------------|
| 1/2"   | 05 61 801 D | 240 | B    |             | 20 (10) | <b>24389</b> |
| 3/4"   | 05 61 802 D | 240 | B    |             | 10 (5)  | <b>24390</b> |
| 1"     | 05 61 803 D | 240 | B    |             | 8       | <b>24391</b> |
| 1 1/4" | 05 61 804 D | 240 |      |             |         | <b>24392</b> |
| 1 1/2" | 05 61 805 D | 240 | C    |             | 6       | <b>24393</b> |
| 2"     | 05 61 806 D | 240 | D    |             | 8       | <b>24394</b> |



Seats / asientos: PTFE<sup>2</sup>  
O-rings / juntas: EPDM  
150 psi @ 73°F

#### SOCKET - CEMENTAR

| Size       | Reference    | psi | Pack | Weight (lb) | Q     | Code         |
|------------|--------------|-----|------|-------------|-------|--------------|
| 2 1/2"     | 05 61 907 MA | 150 | D    |             | 4 (1) | <b>07386</b> |
| 3"         | 05 61 908 MA | 150 | D    |             | 2 (1) | <b>07387</b> |
| 4" (DN 80) | 05 61 910 MA | 150 | D    |             | 2 (1) | <b>07388</b> |
| 4"         | 05 61 911 MA | 150 | D    |             | 1     | <b>24396</b> |

#### THREADED - ROSCAR

| Size       | Reference | psi | Pack | Weight (lb) | Q     | Code         |
|------------|-----------|-----|------|-------------|-------|--------------|
| 2 1/2"     | 05 61 807 | 150 | D    |             | 4 (1) | <b>07396</b> |
| 3"         | 05 61 808 | 150 | D    |             | 2 (1) | <b>07397</b> |
| 4" (DN 80) | 05 61 810 | 150 | D    |             | 2 (1) | <b>07398</b> |
| 4"         | 05 61 811 | 150 | D    |             | 1     | <b>24395</b> |

<sup>1</sup> 1/2" thru 2" Ball Valves are supplied with both socket and threaded end connectors.

<sup>2</sup> 2 1/2" thru 4" Ball Valves can be ordered with either socket or threaded connections, they don't include both.

<sup>1</sup> 1/2" hasta 2" la válvula es entregada con manguitos cementar y roscar..

<sup>2</sup> 2 1/2" hasta 4" la válvula debe ser pedida con uniones cementar o roscar (no ambas).