




S9GO01 • HGO201 BEIGE
24x24 in 60x60 cm

S9GO05 • HGO205 GRAY
24x24 in 60x60 cm

S9GO08 • HGO208 NERO
24x24 in 60x60 cm

Special Pieces



S8GO01G • Step / HGO201 BEIGE
12x24 in 30x60 cm 

S8GO05G • Step / HGO205 GRAY
12x24 in 30x60 cm 

S8GO08G • Step / HGO208 NERO
12x24 in 30x60 cm 



S8GO01C • Pool Coping with full round edge / HGO201 BEIGE
12x24 in 30x60 cm 

S8GO05C • Pool Coping with full round edge / HGO205 GRAY
12x24 in 30x60 cm 

S8GO08C • Pool Coping with full round edge / HGO208 NERO
12x24 in 30x60 cm 



THICKNESS
0.79"
20 mm



FREEZE / THAW
RESISTANT
ASTM C 1026



WATER ABSORPTION
~0,1%
ASTM C 373



RECOMMENDED USE




CHEMICAL/STAIN RESISTANCE
Class: A
ASTM C 650
Class: A
ASTM C 1378



BREAKING STRENGTH
≥3400 lbs.
ASTM C 648




SLIP RESISTANCE
≥0.60
ANSI 137.1 (DCOF)

PACKAGING 24x24 in

Pcs. 66
Sq.Ft. 255.75
Lbs. 2380



SHADE VARIATION



Digital HD
Porcelain Tiles



due 2



Del Conca USA, Inc. - 155 Del Conca Way - Loudon, TN 37774 - USA
Tel 865.657.3550 - Fax 865.657.3554
www.delconcausa.com - sales@delconcausa.com

