



ECOSMART POU models are designed for single point of use applications such as hand sinks, and low flow rates not exceeding 0.5 gallons per minute. Because of their compact size they can easily fit under a sink, cabinet or very small area. They are easy to install, durable and made of top quality materials. The heat exchanger is made out of stainless steel and the heating elements are copper and brass. They are easily replaceable in the field, different than other point of use in the market today that require replacing a custom made cartridge or complete exchanger.

ENJOY Reliably Endless Hot Water with ECOSMART tankless water heaters.

| Temperature Rise at | .50 GPM | .75 GPM | 1.0 GPM |
|---------------------|---------|---------|---------|
| Eco POU 3.5 | 47° | 31° | 24° |
| Eco POU 6 | 74° | 49° | 37° |

| IDEAL FOR | |
|------------------|--------------------------|
| Office Buildings | Hotel |
| Gas Stations | Warehouses |
| Retail stores | Medical Offices |
| Schools | Restaurants |
| Malls | Manufacturing Facilities |
| Motels | Boats & more..... |

| MODELS | POU 3.5 | POU 6 |
|----------------------|---------------|---------------|
| Phase | 1 | 1 |
| Voltage | 120 | 208/240 |
| Wattage | 3.5 KW | 6 / 8 KW |
| Amperage | 29 | 28.8 /33 |
| Required breaker | 30 | 30 /40 DP |
| Required wire | 10 | 10 |
| Min flow to activate | .25 | .25 |
| Dimensions | 7" x 11" x 3" | 7" x 11" x 3" |
| Weight | 4lb | 4lb |
| Water Connections | 1/2" NPT | 1/2" NPT |