

# RZWS

Size: **10", 18", 36"**  
Flow: **0.25 or 0.50 GPM**

### FEATURES

- Patented StrataRoot™ baffles divert water to the root zone while adding strength to the unit
- Durable locking cap
- Pressure-compensating bubbler
- Built-in Hunter Swing Joint for direct installation to ½" PVC fitting
- Pre-assembled watering system for fast installation
- Warranty period: 2 years

### OPERATING SPECIFICATIONS

- Bubbler flow rates: 0.25 or 0.50 GPM
- Recommended pressure range: 15 to 70 PSI

### FACTORY INSTALLED OPTIONS

- Check valve
- Locking reclaimed purple cap

### USER INSTALLED OPTIONS

- Fabric sleeve that helps prevent soil intrusion in sandy areas for 18" and 36" models (P/N RZWS-SLEEVE)
- Replacement cap for 18" and 36" models (P/N 913300SP)
- Locking reclaimed purple cap for 18" and 36" models (P/N 913301SP)
- Reclaimed water purple cap for 10" (P/N RZWS10-RCC)



#### RZWS-10

Diameter: 2"  
Length: 10"

#### RZWS-18

Tube Diameter: 3"  
Cap Diameter: 4.75"  
Length: 18"

#### RZWS-36

Tube Diameter: 3"  
Diameter: 4.75"  
Length: 36"

#### RZB

The RZB is an accessory for small trees and shrubs that assists irrigation systems in delivering water to the roots.

Solid mesh tube with perforated top to complement overhead or drip irrigation systems

Allows oxygen and natural precipitation to reach the root zone

Easy installation that directs overhead and drip irrigation to the root zone



Diameter: 2"  
Length: 9"



**Reclaimed models available**  
**Add -R to model number**

### ROOT ZONE WATERING SYSTEM - SPECIFICATION BUILDER: Order 1 + 2 + 3

1 Model	2 Bubbler Flow Rate	3 Options
RZWS-10 = 10" Root Zone Watering System	25 = 0.25 GPM	(blank) = No option
RZWS-18 = 18" Root Zone Watering System	50 = 0.50 GPM	CV = Check valve
RZWS-36 = 36" Root Zone Watering System	(blank) = No bubbler or swing joint	R = Reclaimed cap
		CV-R = Check valve with reclaimed cap

#### Examples:

RZWS-18 - 25 = 18" Root Zone Watering System at 0.25 GPM

RZWS-10 - 50 - CV = 10" Root Zone Watering System at 0.50 GPM, with check valve

RZWS-36 - 25 - CV-R = 36" Root Zone Watering System at 0.25 GPM, with check valve and reclaimed cap

### ADDITIONAL OPTIONS (SPECIFY SEPARATELY)

RZWS-SLEEVE = Field-installed sleeve made from filter fabric