

MODEL: PE153



3-CIRCUIT DIGITAL CONTROL

IN TYPE 3R RAINPROOF ENCLOSURE, FOR INDOOR/OUTDOOR USE

SUITABLE FOR SWIMMING POOL/SPA APPLICATIONS.

IMPORTANT: This installation is subject to the approval by the local inspection authority.

USE COPPER CONDUCTORS ONLY. Do not exceed the maximum ratings of individual components and current carrying capacity of conductors. For grounding of the installation, refer to Article 250 and 680 of the National Electrical Code (for Canadian installations; Section 10 and 68 of the Canadian Electrical Code). This Control should not be connected to any equipment which would cause bodily injury or property damage should it be activated unexpectedly. After wiring, replace insulator before turning on electricity.

KEEP DOOR CLOSED AT ALL TIMES.

SEE OWNERS MANUAL FOR OPERATION INSTRUCTIONS.

3-CIRCUIT DIGITAL CONTROL RATINGS:

CLOCK SOURCE VOLTAGE: 120/240 VAC, 50/60 Hz.

POWER CONSUMPTION: 6.0 Watts Max.

CONTACT RATINGS (SPST) - EACH CIRCUIT

- 17A Resistive - 120/240V AC
- 17 Full Load A, 80 Lock Rotor A - 120/240V AC
- 5A Tungsten, or Ballast 120/240V AC
- Aux Switch: 2A, 24V AC

INTERMATIC INCORPORATED

SPRING GROVE, ILLINOIS 60081-9698

158PE11966